

S/182/60/000/011/003/016 A161/A029

Development of Technology for Manufacture of Hollow Axles




Fig. 4: Die for plan-bearings axle: a) die; b) forging; c) mandrel

Card 6/8

S/182/60/000/011/003/016 A161/A029

Development of Technology for Manufacture of Hollow Axles




Fig. 5: Die for roller bearing axle: a) die; b) forging

Card 7/8

S/182/60/000/011/003/016 A161/A029

Development of Technology for Manufacture of Hollow Axles




Fig. 7: Hollow axle for plain bearings: a) after forging; b) after machining; c) ready axle in cross section view


Card 8/8


SHIFRIN, M. Yu.

Increasing the output of wheel-rolling mills. Metallurg 6 no.5:28-29 My '61. (MIRA 14:5)

l. Ukrainskiy nauchno-issledovatel'skiy trubnyy institut. (Rolling mills) (Wheels)

。 1989年,1980年的1980年,1980年的1980年,1980年,1980年,1980年,1980年的1980年,1980年的1980年,1980年的1980年,1980年的1980年,1980年的1980年,1






Rolling Industry; Handbook

Institutes, and planning and design organizations. It may also be used by students at schools of higher education.

COVERACE: Volume 2 of the handbook reviews problems connected with the preparation of motal for rolling, the quality and quality control of rolled products, and designs of roll passes in morehant mills. The following topics are discussed; processes of manufacturing semifinished and finished rolled products (the rolling of blooms, billets, shapes, beams, rolled products (the rolling of blooms, billets, shapes, beams, rails, strips, wire, plates, sheets, and the drawing of steel wires and by different methods, and special types of rolled products. Problems of the organization of rolling operations are reviewed, and types of rolled products manufactured in the USSR are shown. No personalities are mentioned. There are no references.

TABLE OF CONTENTS:[Abridged]:

Card 3/14



SHIFRIN, M.Yu.; PINENOV, A.R.

Barrel shape forming during the upsetting of hollew blanks.

Barrel shape forming during the upsetting of hollew blanks.

Kuz.-shtam.proizv. 5 no.7:13-15 Jl '63. (MIRA 16:9)

SHIFRIN, M.Yu.; PIMENOV, A.R.


Piercing rectangular ingots in a round container. Kuz.-shtam.proizv.
(MIRA 16:9)
5 no.8:11-15 Ag '63.

SHIFRIN, N. Yu., kand. tekhn. neda; Volkovitskiy, G.I., kand. tekhn. nauk; KOFALKIK, B.F., kand. tekhn. nauk; KOVALKIKO, Yu.Ye., kand. tekhn. nauk; BOTALKOTA, F.K., lnzh. nauk; BOTALA H.I., ingh.; POLYAKOTA, F.K., lnzh. Manndacturing hollow railroad axles from centrifugally cast billeti. Proizv. trub no.12:133-126 162. (MIGA 17:11)

## SHIFRIN, M.Yu.

Zone of sticking during the upsetting of hollow cylindrical blanks. Izv. vys. ucheb. zav.; chern. met. 8 no.9:129-132 165. (MIRA 18:9)

1. Ukrainskiy nauchno-issledovatel skiy trubnyy institut.



## SHIFRIN, N.K.

Problems and methods in hygiene based on I.P. Pavlov's teaching. Gig.sanit., Moskva no.3:3-9 Mar 1951. (CIML 20:7)

1. Professor. 2. Gor'kiy.

- 1. SHIFRIN, N.K.; BELIAYEV, I.I.
- 2. USSR (600)
- 4. Cherkinskiy, S.N.
- 7. "Communal hygiene." Cherkinskiy, an article published in vol. 2 of the Great Soviet Encyclopedia, 2d ed., 1952, Reviewed by N.K. Shifrin, I.I. Beliaev. Gig. i san. no. 3, 1953.

9. Monthly List of Russian Accessions, Library of Congress, APRIL 1953, Uncl.

SHIFRIN, N.K., professor; AVERBAKH, M.F., inzhener

Hygienic evaluation of standard plan for machine-tractor station shops. Gig. i san. 21 no.4:27-31 Ap 156. (MIRA 9:7)

hyg. aspects of shops in tractor stations (Rus))

SOV/137-58-9-20338

Ye.L.

Translation from: Referativnyy zhurnal, Metallurgiya, 1958, Nr 9, p 318 (USSR)

AUTHOR: Shifrin, N.K.

TITLE: Certain Problems on the Physiology of Labor Upon the Intro-

duction of New Technique in Industry (Nekotoryye voprosy

fiziologii truda pri vnedrenii novoy tekhniki na proizvodstve)

PERIODICAL: V sb.: Materialy po vopr. gigiyeny truda i kliniki prof.

bolezney. Gor'kiy, 1957, pp 3-10

ABSTRACT: An examination of the problems of the physiology of labor

and measures intended to eliminate factors adversely affecting the health of the workers upon the employment of high-


frequency heating, pneumatic hand tools, and high-speed


cutting.

1. Labor--Physiological factors 2. Industrial equipment

-- Physiological effects

Card 1/1





USSR/Mining Methods Ore Dressing

عب عات وبالتباتليّانات

Jul 48

"Let Us Pay More Attention to Dressing 'Self-Fluxing' Ore at the Krivoy Rog Mines," S. D. Shifrin, Engr, 1 p

"Gor Zhur" No 7

Process of "self fluxing" ore is predetermined by physical properties of the ore and the impurity of rocks. Gives several methods for dressing mineral rock. Points out necessity for arranging light dressing installations on the basis of practical experience at Ural mines. Recommends such installations at Krivoy Rog-mines.

33/49188

SHIFRIN, Semen Markovich

(Leningrad Construction Engineering Inst) Academic degree of Doctor of Technical Sciences, based on his defense, 23 April 1955, in the Council of the All-Union Sci Res Inst of Water Supply, Sewerage, Hydraulic Engineering, and Engineering Hydrology, of his dissertation entitled: "Purification of sewage by the method of settling."

Academic degree and/or title: Boctor of Sciences

SO: Decisions of VAK, List no. 21, 22 Oct 55, Byulleten' MVO SSSR, No. 19, Oct 56, Moscow, pp. 13-24, Uncl. JPRS/NY-536

#### CIA-RDP86-00513R001549410014-2 "APPROVED FOR RELEASE: 08/25/2000

. SHIFRIN, S.M.

USSR Chemical Technology. Chemical Products and Their I-12 Application--Nater treatment. Sewage water

Abs Jour: Ref Zhur-Khimiya, No 3, 1957, 9150

Author : Shifrin, S. M.
Inst : Not given Title : A New Method for Designing Vertical-Flow Sewage

Settling Tanks for a Given Degree of Clarification

of the Sewage Liquid

Orig Pub: Vodosnabzheniye i san. tekhnika, 1955, No 2, 27-31

Abstract: A method is proposed for the design of verticalflow sewage settling tanks based on the assumption

that the dispersed solids settle from the sewage water (SW) not during its upward flow in the cylindrical section of the settling tank (as it custom-arily assumed) but during the radial motion of the SW (on leaving the circular slit) between the lower edge of the cone of the vertical pipe and the inclined surface of the deflecting plate. The author

Card 1/2

APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R001549410014-2"

Card 2/2

SHIFRIN, S.M.; ASS, M.I.

Investigation of the functioning of a methane sewage tank with a floating cover under mesophilic and thermophilic conditions. Vod. floating tower under mesophilic and thermophilic conditions. Vod. (MIRA 8:12) i san. tekh. no.4:23-26 Jl'55. (Sewage disposal)

SOV/124-57-5-5790

Translation from: Referativnyy zhurnal. Mekhanika, 1957, Nr 5, p 107 (USSR)

Shifrin, S. M., Ivanov, G. V. AUTHORS:

Analog Simulation of Vertical Settling Tanks (Modelirovaniye TITLE:

vertikal'nykh otstoynikov)

PERIODICAL: Nauch. tr. Leningr. inzh.-stroit. in-ta, 1955, Nr 20, pp 38-58

ABSTRACT: Description of a laboratory method and the results derived therefrom are given relative to the investigation of vertical settling tanks with the aim of developing an efficient system of settling tanks for the sewerage-purging system of the Leningrad Meat-processing Plant currently being rebuilt (8 vertical circular settling tanks of usual design with a 6-m diameter and an 8-m height). The investigations were conducted at the laboratory of the LISI (Leningrad Structural Engineering Institute) with the aid of a model manufactured out of plexiglas and scaled to 1:15. The simulation was conducted according to the A. G. Averkiyev method (Vses. n.-i. in-t gidrotekhn., 1952) based on the analog simulation of a free surface with the substitution of a pressure flow for the free-surface flow. The authors consider it feasible to evaluate the hydraulic performance characteristic of the

Card 1/2

SOV/124-57-5-5790

Analog Simulation of Vertical Settling Tanks

settling tank according to the coefficient of water circulation, i.e., the ratio of the sum total of the transient and twice the circulatory discharge of water divided by the transient discharge at the characteristic cross section of the settling tank.

Kh. A. Navoyan

Card 2/2

NAVROTSKIY, Georgiy, Aleksandrovich, kandidat tekhnicheskikh nauk; RUSKEVICH, Nikhail Leont'yevich; SHIFRIN, S.M., nauchnyy redaktor; BUKOVA, I.V., redaktor; EGGERT, A.P., tekhnicheskiy redaktor

[Automatic cold upsetting machinery] Kholodnovysadochnye avtomaty.

Moskva, Vses. uchebno-pedagog. izd-vo Trudrezervizdat, 1956. 68 p.

(Metal working machinery) (MLRA 9:7)

SHIFRIN Semen Markovich, doktor tekhnicheskikh nauk, professor; SHIGORIN, G.G., kandidat tekhnicheskikh nauk, nauchnyy redaktor; KAPLAN, M.Ya., redaktor izdatel'stva; PUL'KINA, Ye.A., tekhnicheskiy redaktor

[Modern methods for mechanical purification of sewage] Sovremennye sposoby mekhanicheskoi ochistki stochnykh vod. Leningrad, Gos. izd-vo lit-ry po stroit. i arkhit., 1956. 179 p. (MLRA 10:4) (Sewage--Purification)

#### CIA-RDP86-00513R001549410014-2 "APPROVED FOR RELEASE: 08/25/2000

SHIFRIN, S.M.

USSR /Chemical Technology. Chemical Products

H-5

and Their Application

Water treatment. Sewage water.

Abs Jour: Referat Zhur - Khimiya, No 1, 1958, 1750

: Shifrin S.M. Author

: Leningrad Institute of Civil Engineering Inst

Modern Methods of Clarifying Sewage Water Title

Sb.: 15-ya nauchn. konferentsiya Leningr. inzh. Orig Pub:

stroit. in-ta, L., 1957, 213-216

A method has been worked out for the calculation Abstract:

of vertical settling tanks (S), which takes into account the inflow velocity of sewage water to the S through the annular cross-section between the end of the funnel shaped central pipe (CP) and the baffle plate. This velocity is limited

Card 1/3


H-5

USSR /Chemical Technology. Chemical Products and Their Application Water treatment. Sewage water.

Abs Jour: Referat Zhur - Khimiya, No 1, 1958, 1750

fractions of unity; U, inflow velocity of sewage water to the S, in m/second; Z -- length of S beyond WR, in M; H -- working depth of S in m; Me concentration of CDA in the initial sewage water, in g/m. Total working length of S is L = Z - 3.8 H. When data on concentration of CDA in the initial sewage water are available and the clarification effect to be attained is set, optimal working depth of the S, or its length, is selected according to the local conditions.

card 3/3



SOV/124-58-3-3071

Translation from: Referativnyy zhurnal, Mekhanika, 1958, Nr 3, p 75 (USSR)

AUTHOR: Shifrin, S'M'

TITLE: Design Calculation of Horizontal Sewer Settling Chambers for

a Given Degree of Liquid Clarification (Raschet gorizontalnykh kanalizatsionnykh otstoynikov na zadannyy effekt

osvetleniya stochnoy zhidkosti)

PERIODICAL: Nauchn. tr. Leningr. inzh. -stroit. in-ta, 1957, Nr 25,

pp 14-27

ABSTRACT: The article presents an approximate solution for the pre-

cipitation of suspended matter in two portions of a horizontal sewer chamber: 1) The main portion, 2) the initial portion which includes the turning zone. Graphs are given to permit a quick determination of the chamber parameters when the depth is 1, 1.5, and 2 m and when the degree of clarification is specified, or vice-versa. An example of the calculation is

given.

O. L. Yushmanov

Card 1/1

## SHIFRIN, S.M.

BARSUKOV, A.A., inzh., laureat Leninskoy premii; BORISOV, Yu.S., inzh.;

VAKS, D.I., inzh.; VIADZIYEVSKIY, A.P., doktor tekhn. nauk; orof.,
laureat Stalinskoy premii; GINZBURG, Z.M., inzh.; GLEYZER, Y.Ye.,
inzh.; ZOBIN, V.S., inzh.; KAZAK, M.I., dots.; KAMINSKAYA, V.V.,
kand. tekhn. nauk; KEDRINSKIY, V.N., inzh., laureat Leninskoy
premii; KUCHER, A.M., kand. tekhn. nauk; KUCHER, I.M., kand. tekhn.
nauk; LEVINA, Z.M., inzh.; IUK'YANOV, T.P., inzh.; MOROZOVA, Ye.M.,
inzh.; NOSKIN, P.A., kand. tekhn. nauk, dots.; NIBERG, N.Ya.,
kand. tekhn. nænk; OSTROUMOV, G.A., inzh.; PIOTKIN, I.B., inzh.;
SPIVAK, E.D., kand. tekhn. nauk; SUM-SHIK, M.R., inzh.; SHASHKIN,
P.I., inzh.; SHIFRIN, S.M., inzh.; YAKOBSON, M.D., doktor tekhn.
nauk, prof.; GLINER, B.M., inzh., red.; SOKOLOVA, T.F., tekhn.

[Handbook for mechanics of machinery plants in tow volumes]
Spravochnik mekhanika mashinostroitel nego zavoda v dvukh tomakh.
Vol.1. [Organization and design preparation for repair work]
Organizatsiia i konstruktorskaia podgetovka remontnykh rabot.
Otv. red. toma R.A. Noskin. 1958. 767 p. Moskva, Gos. nauchnotekhn. izd-vo mashinostroit. lit-ry.

(MIRA 11:8)

(Machinery-Maintenance and repair)

SHIFRIN, J.M

AGRANONIK, Ye.Z., kand.tekhn.nauk; BELOV, A.N., dotsent; GLADKOV, A.M., inzh.; GLUSKIN, S.A., inzh.; IVANOV, L.V., dotsent, kand.tekhn. nauk; LIPKIN, Ye.V., kand.tekhn.nauk; NIKIFOROV, G.N., dotsent, kand.tekhn.nauk; PESENSON, I.B., inzh.; PREGER, Ye.A., dotsent, kand.tekhn.nauk; PYATOV, Ya.N., inzh.; ROKHCHIN, Ye.Z., inzh.; FEDOROV, N.F., prof., doktor tekhn.nauk; SHVARTS, R.B., inzh.; SHIGORIN, G.G., dotsent, kend.tekhn.nauk; SHIFRIN, S.M., prof. doktor tekhn.nauk; POPRUGIN, I.V., inzh., retsenzent; KATS, K.F., inzh., retsenzent; ROTENBERG, A.S., red.izd-va; VORONETSKAYA, L.V., tekhn.red.

> [Manual of water-supply engineering and sewerage] Spravochnik po vodosnabzheniiu i kanalizatsii. Pod red. N.F.Fedorova. Leningrad, Gos.izd-vo lit-ry po stroit., arkhit. i stroit.materialam, 1959. 410 p.

> 1. Moscow. Gosudarstvennyy projektnyy institut Vodokanalprojekt. Leningradskoye otdeleniye.

(Water-supply engineering) State Quet Planning Canal Design Lungade Dept.

AGRANONIK, Ye.Z., kand.tekhn.nauk; HELOV, A.N., dotsent; GLADKOV, A.M., inzh.; GLUSKIN, S.A., inzh.; IVANOV, L.V., dotsent, kand.tekhn.nauk; LIPKIN, Ye.V., kand.tekhn.nauk; NIKIFOROV, G.N., dotsent, kand.tekhn.nauk; PESENSON, I.B., inzh.; PREGER, Ye.A., dotsent, kand.tekhn.nauk; PYATOV, Ya.N., inzh.; ROKHCHIN, Ye.Z., inzh.; FEDOROV, N.F., prof., doktor tekhn.nauk; SHVARTS, R.B., inzh.; SHIGORIN, G.G., dotsent, kand.tekhn.nauk; SHIFRIN, S.M., prof., doktor tekhn.nauk; ROTENBERG, A.S., red.izd-va; VORONETSKAYA, L.V., tekhn.red.

[Water-supply and sewerage manual] Spravochnik po vodosnabzheniiu i kanalizatsii. Pod red. N.F.Fedorova. Izd.2., ispr. i dop. Leningrad, Gos.izd-vo lit-ry po stroit., arkhit. i stroit.materialam, 1960. 420 p. (MIRA 13:12)

1: Moscow. Vodokanalproyekt. Leningradskoye otdeleniye. (Water-supply engineering) (Sewerage)

FEDOROV, N.F.; SHIFRIN, S.M.; SHIGORIN, G.G.; PESENSON, I.B.; MORGENSHTERN, V.S., kand. tekhn. nauk, nauchnyy red.; KAPLAN, M.Ya., red. izd-va; PUL'KINA, Ye.A., tekhn. red.

[Sewerage systems and structures; planning and design] Kanalizatsionnye seti i sooruzheniia; proektirovanie i raschet. Leningrad, Gos. izd-vo lit-ry po stroit., arkhit. i stroit. materialam, 1961. 314 p.

(MIRA 14:7)

(Sewerage)

SHIFRIN, Semen Markovich, doktor tekhn.nauk; IVANOV, Gleb Valerianovich, kand.tekhn.nauk; KOMAROVSKIY, M.F., red.; FREGER, D.P., red. izd-va; GVIRTS, V.L., tekhn.red.

[Glarifier with natural aeration for the purification of waste waters] Osvetlitel's estestvennoi aeratsici dlia ochistki stochnykh vod. Leningrad, 1961. 17 p. (Leningradskii Dom nauchno-tekhnicheskoi propagandy. Chmen peredovym opytom. Seriia: Stroitel'naia promyshlennost', no.14)

(MIRA 14:12)

(Sewage--Purification)

SHIFRIN, S.M. (Leningrad); ASS, M.I. (Leningrad); DUAN FU-LIN (Leningrad)

Effect of high gas pressure under the charge hole of blast furnaces on the operation of radial clarifying tanks. Vod.

i san. tekh. no.10:20-22 0 '61.

(Water--Purification)

(Blast furnaces)

SHIFRIN, Semen Markovich, doktor tekhn. nauk, prof.; ZEL'DOVICH,
Rafail Nekhem'yevich, , kand. ekonom. nauk, dots.; DANILOV,
Petr Mikhaylovich, ekonom.; REZNIK, A.I., red.; UCHITEL',
I.Z., red. izd-va; LEIYUKHIN, A.A., tekhn. red.

[The economics of water supply and sewerage management and construction] Ekonomika vodoprovodno-kanalizatsionnogo khoziaistva i stroitel'stva. Pod obshchei red. S.M.Shifrina. Moskva, Izd-vo M-va kommun.khoz.RSFSR, 1962. 357 p.

(MIRA 15:11)

(Water supply) (Sewerage)

SHIFRIN, S.M., doktor tekhn. nauk, prof., otv. red.

TO SEE THE THE PROPERTY OF THE

[Water supply and sewerage; reports of the 20th Scientific Conference] Vodosnabzhenie i kanalizatsiia; doklady XX nauchnoi konferentsii. Leningrad, 1962. 96 p. (MIRA 16:2)

1. Leningrad. Inzhenerno-stroitel'nyy institut. Nauchnaya konferentsiya.

(Water-supply engineering) (Sewage--Purification)

SHIFRIN, S.M., doktor tekhn. nauk; SOLOMAKHIN, I.I., inzh.

Purifying the waste waters of meat-packing plants. Vod. i san.
tekh. no.4:18-21 Ap '64 (MIRA 18:1)

SHIFRIN, S.M., doktor tekhn. nauk (Leningrad); BURTSEV, V.P., inzh. (Leningrad)

Purification of waste waters of cheese factories. Vod. i san. tekh. no.10:30-32 0 165. (MIRA 18:11)

KOZ'YAKOV, N.I.; SHIFRIN, S.S.; LAPTEV, I.D., red.; GOL'DBERG, M.L., red.; VESKOVA, Ye.I., tekhn.red.

[For the highly profitable operation of each state farm]
Za vysokodokhodnuju rabotu kazhdogo sovkhoza. Moskva, Gos.
izd-vo sel'khoz.lit-ry, 1956. 278 p. (MIRA 13:1)

1. Deystvitel'nyy chlen Vsesoyuznoy Akademii sel'skokhozyaystvennykh nauk im. V.I.Lenina (for Laptev).

(State farms)

APROSINA, Z.G., kand.med.nauk, SHIFRIN, S.S.

Cholecystography and results in Botkin's disease. Sov.med. 22 (MIRA 11:10) no.8\$21-27 Ag '58

1. Iz kafedry obshchey i gospital noy terapii sanitarno-gigiyenicheskogo fakul teta (zav. - deystvitel nyy chlen AMN SSSR prof. Ye.M. Tareyev) i kafedry rentgenologii i radiologii (zav. - prof. P.D. Yal tsev) I Moskovskogo Ordena Lenina meditsinskogo instituta imeni I.M. Sechenova. (HEPATITIS, INFECTIOUS, pathol.

liver changes, value of cholecystography (Rus)) (CHOLECYSTOGRAPHY, in various distinct cirrhosis (Rus))

SHIFRIN, S.S.


Experience in the use of radioactive phsophorus for the diagnosis of cancer of the cervix uteri. Sov.med. 23 no.8:94-98 Ag 159.

(MIRA 12:12)

1. Iz kafedry akusherstva i ginekologii (zav. - prof. K.N. Zhmakin) i kafedry rentgenoradiologii (ispolnyayushchiy obyazannosti zavedu-yushchego kafedroy - kand.med.nauk I.I. Fedorov) I Moskovskogo ordena Lenina meditsinskogo instituta imeni I.M. Sechenova.

(PHOSPHORUS radioactive) (CERVIX UTERI neoplasms)

SHIFRIN, S. S., Cand Med Sci (diss) -- "The accumulation of radioactive phosphorus in tumors, and the possibility of using radiometric investigation for diagnosing cancer of the cervix uteri". Moscow, 1960. 15 pp (First Moscow Order of Lenin Med Inst im I. M. Sechenov), 200 copies (KL, No 10, 1960, 138)



MECURINOV, R.A.; SHIPPIN, S.S.

1-ray diagnosis of late sequelae of a closed cranial trauma in children. Chur. nevr. i psikh. 64 no.7:1010-1015 

(MIRA 17:12)

1. Kafedra nervnykh beleznye (zavaduyushchiy - prof. V.V. Mikheyev)

/ Mozkovskogo ordena lenina meditsinskogo instituta im. T.Y.

Sechenova.

SHIPRIN, S.S., Lind. aed. nouk

Large examination in servical osteochondrosis. Trudy 1-go MMI 38:211220 165. (MIRA 18:10)

SHTUL'MAN, D.R., assistent; SHIFRIN, S.S., kand. med. nauk; KOLOMOYTSEVA, I.P., assistent; RUMYANTSEV, Yu.V.

Chinical and roentgenological correlations in discogenic cervical myelopathy. Trudy 1-go MMI 38:235-246 '65. (MIRA 18:10)

RUMYANTSEV, Yu.V.; SHIFRIN, S.S., kand. med. nauk

Myelography in discogenic cervical myelopathy. Trudy 1-go MMI 38:247258 165.

(MIRA 18:10)

AISTOV, N.N., prof., doktor tekhn. nauk; VASIL'YEV, B.D., prof., doktor tekhn. nauk; IVANOV, V.F., prof., doktor tekhn. nauk; SAKHNOVSKIY, K.V., prof., doktor tekhn. nauk; SMIRNOV, N.A., prof.; ORLOV, A.I., dots., kand. tekhn. nauk; SHIFRIN, S.M., prof., doktor tekhn. nauk; Prinimali uchastiye: AKIMOVA, L.D., kand. tekhn. nauk, dots.; SPIRIDONOVA, O.M., kand. tekhn. nauk, dots.; MAKUKHIN, V.L., nauchnyy red.; STAROVOYTOV, I.F., inzh., red. izd-va; PUL'KINA, Ye.A., tekhn. red.


[The history of building practices] Istoriia stroitel'noi tekhniki. [By] N.N.Aistov i dr. Pod obshchei red. V.F.Ivanova. Leningrad, Gosstroiizdat, 1962. 560 p. (MIRA 15:12)


1. Chlen-korrespondent Akademii stroitel'stva i arkhitektury SSSR (for Vasil'yev, Sakhnovskiy).

(Building)

SHIFRIN, T.A., inshener.

Over-all mechanization of small capacity factory boilers. Stroi.i dor.machinostr. i no.1:30-33 Ja '56. (MIRA 10:1) (Boilers)







RYAKHIN, V.A., kand.tekhn.nauk; ZAYTSEV, L.V., insh.; SHIFRIN, T.A., insh.

Effectiveness of the specialized manufacture of standardized series of excavators and cranes. Stroi. i dor. mash. 10 no.7:1-3 Jl '65.

(MIRA 18:8)





SHAN'GIN, N.V.; SHIFRIN, V.Ya.

Relation between the speed of a linear wave and porosity and its use in ultrasonic seismic logging of boreholes. Uch.zap.IGU (MIRA 15:11) no.303:152-166 '62. (Seismic prospecting) (Porosity)

#### "APPROVED FOR RELEASE: 08/25/2000 CIA-

CIA-RDP86-00513R001549410014-2

SHIFRIN, V. L.

PA 12/49T68

USSR/Engineering Peat Industry Peat - Drying

Aug 48

"Problems of Laying Out Subconveyor Belts for the Removal of Cut Peat by the UMPF-4 Machines," V. L. Shifrin (Giprotorf),  $1\frac{1}{4}$  pp

"Torf Prom" No 8

Describes new scheme for drying cut peat.

12/49168

Peat

Volume weight of cut peat in the stacks. Torf. prom. 29 no. 5, 1952.

9. NONTHLY LIST OF RUSSIAN ACCESSIONS, Library of Congress, August 1952, Uncl.

Peat Industry

Extent of technological estimates in designing peat enterprises. Torf. prom, 29, No. 8, 1952.

Monthly List of Russian Accessions, Library of Congress, October, 1952. UNCLASSIFIED.

SHIFRIN, V. L., Eng.

Peat Bogs

Mathematical method of determining reserves in peat deposits. Torf. prom. 29 No. 9, 1952.

Monthly List of Russian Accessions, Library of Congress, December, 1952. UNCLASSIFIED.

SHIFRIM, V.L., inzhener.

Method for the determination of peat reserves with the aid of aerial photographs. Torf.prom. 34 no.5:24-28 '57. (MIRA 10:10) (Peat bogs) (Photography, Aerial)

SHTERN, A.A.; SHIFRIN, Y.A. [Shyfrin, I.A.], inzh.

First Soviet firm. Leh.prom. no.1:6-9 Ja-Mr '62. (MIRA 15:9)

1. L'vovskaya obuvnaya firma "Progres". 2. Glavnyy inzh.
L'vovskoy obuvnoy firmy "Progres" (for Shtern).

(Lvov economic region—Shoe industry) (Industrial organization)

SHUBARIN, Yuriy Vasil'yevich; MISHCHENKO, Yu.A., dotsent, retsenzent;
SHIFRIN, Ya.S., dotsent, retsenzent; TERESHCHENKO, A.I., dotsent, otv.red.; BAZILYANSKAYA, I.L., red.; NIKULINA, N.I., tekhred.

[Microwave antennas] Antenny sverkhvysokikh chastot. Khar'kov, Izd-vo Khar'kovskogo gos.univ., 1960. 283 p.

(MIRA 14:1)

(Antennas (Electronics))

30292 \$/109/61/006/011/007/021 D266/D305

9,1914

AUTHOR: S

Shifrin, Ya.S.

TITLE:

Correlation characteristics of the radiation patterns

of linear antennas

PERIODICAL:

Radiotekhnika i elektronika, v. 6, no. 11, 1961,

1846 - 1858

TEXT: The purpose of the paper is to determine the correlation in a particle of the radiation pattern, and to calculate the probability that in certain directions (at the maxima of the side-lobes) the amplitude of the radiation pattern does not exceed predetermined value. It is assumed that the random errors influence only the phase of the electric field. In the absence of any errors the phase along the antenna is taken to be constant, i.e. the distribution function, A(x) is assumed real. The random phase errors are represented by a function  $\varphi(x)$  (assumed to be small) whose average is zero. The fluctuation of the radiation pattern is then obtained in the following form:

Card 1/84

30292 S/109/61/006/011/007/021 D266/D305

Correlation characteristics of ...

$$\angle f(\psi) = \Im \int_{-\infty}^{\infty} \varphi(x) A(x) e^{j\psi x} dx \qquad (2)$$

where  $\psi = \frac{1}{2} \sin \theta$ ;  $\theta =$ angle between the normal to the system and the direction of the point investigated,  $\lambda$  - wavelength, L - length of the antenna,  $f(\psi)$  - radiation pattern. The correlation function of  $f(\psi)$  is defined as follows  $K_{\underline{i}}(\psi, \psi_{\underline{i}}) = \bigwedge f(\psi) \bigwedge f(\psi_{\underline{i}}). \tag{3}$ 

$$\mathbf{K}_{\tau}(\boldsymbol{\psi}_{i} \, \boldsymbol{\psi}_{1}) = \Delta \mathbf{f}(\boldsymbol{\psi}) \Delta \mathbf{f}^{*}(\boldsymbol{\psi}_{1}). \tag{3}$$

Introducing furthermore the relationship

$$\varphi(x) \varphi(x_1) = rd(x) d(x_2)$$

where r = coefficient of correlation and  $\sigma^2$  = mean square of the phase distribution  $\sigma^2(x) = \varphi^2(x)$ . The coefficient of correlation is assumed in the following form:

 $-\omega(x-x_0)^2/\sigma^2$ 

Card 2/84

30292 S/109/61/006/011/007/021 D266/D305

Correlation characteristics of ...

$$P_{k} = e^{-\frac{\left\{v \left(\psi_{k}\right)\right\}^{1+\tilde{a}_{k}^{2}}}{2\sigma_{k}^{2}}} \sum_{n=1}^{\infty} \left(\frac{v \left(\psi_{k}\right)}{\bar{a}_{k}}\right)^{n} I_{n} \left(\frac{\bar{a}_{k} v \left(\psi_{k}\right)}{\sigma_{k}^{2}}\right). \tag{15}$$

where

$$\bar{a}_{k} = \int_{-1}^{+1} A(x) \cos \psi_{n} \times dx$$

and  $\mathbf{1}_n$  - modified Bessel function of the n-th order. After a number of simplifying assumptions, the author derives the following simple formula for the probability that none of the side-lobes exceed the theoretical value

$$P = 0.25^{N}$$
 (20)

where N is the number of side-lobes investigated. As a concrete example the effect of manufacturing tolerance is discussed. There are 5 figures and 8 references: 7 Soviet-bloc and 1 non-Soviet-b SUBMITTED: May 10, 1961 card 4/34

30292 S/109/61/006/011/007/021 D266/D305

Correlation characteristics of ...

where c = 2 $\rho$ /L and  $\rho$  is the correlation interval. With these assumptions an analytical solution is obtained for the correlation function. The normalized correlation function,  $R_f$  is plotted in Fig. 1 against  $\P$  for  $\P_1$  = 0 and for various values of the parameter c. It can be seen that for large values of c the absolute value of  $R_f$ (0,  $\P$ ) is very near to unity. In practical cases  $\rho$  is of the order of  $\P$  while L is much larger than  $\P$ , therefore call. In this case the normalized correlation function has the simple form

$$R_{f}(\gamma; \psi_{1}) \stackrel{\text{sin}(\psi - \psi_{1})}{= \psi_{1}}. \tag{11}$$

The author next considers the problem that what is the probability  $P_k$  that in the direction  $\mathcal{T}_k$  the amplitude of the radiation pattern exceeds v( $\psi_k$ ). The result is obtained in the form


Card 5//5 4

SHIFRIN, Ya.S. (Khar'kov)

Effect of fluctuations in an incident wave on the diffraction pattern in the focal plane of a lens. Akust.zhur. 7 no.2:248-255 161.

(MIRA 14:7)

(Wave motion, Theory of) (Diffraction)



1.

li3206 5/046/62/008/004/010/017 B108/B186

AUTHOR:

Shifrin, Ya. S. (Khar'kov)

TITLE:

Correlation characteristics of a diffraction pattern

produced by a focusing system

PERIODICAL:

Akusticheskiy zhurnal, v. 8, no. 4, 1962, 460-465

TEXT: The correlation function for the diffraction field in the focal plane of a paraxial focusing system is calculated. Expanding the transverse correlation function of the field (L. a. Chernov. Rasprostraneniye voln v srede so sluchaynymi neodnorodnostyami - Propagation of waves in a medium with random inhomogeneities - M., Izd-vo AN SSSR, 1958; Akust. zh., 1957, 3, 2, 192-194) into a series with regard to the mean square fluctuations  $\alpha$  of amplitude and phase, the normalized correlation function assumes the form

$$R = \frac{\sum_{m=1}^{\infty} \frac{\alpha^{m}}{m!} I(c_{m}, \psi_{1}, \psi_{2}) I(c_{m}, \psi_{3}, \psi_{4})}{\sqrt{\sum_{m=1}^{\infty} \frac{\alpha^{m}}{m!} I_{0}(c_{m}, \psi_{1}) I_{0}(c_{m}, \psi_{2}) \sum_{m=1}^{\infty} \frac{\alpha^{m}}{m!} I_{0}(c_{m}, \psi_{2}) I_{0}(c_{m}, \psi_{4})}},$$
 (5)

Card 1/2

S/046/62/008/004/010/017 B108/B186

Correlation characteristics of a...

where  $c_m=rac{2a}{\sqrt{mh}}$ ,  $\psi_1=rac{khy'}{2f}$ ,  $\psi_2=rac{khy''}{2f}$ ,  $\psi_3=rac{khz'}{2f}$ ,  $\psi_4=rac{khz''}{2f}$ .

and where, e.g.,  $I_0(c_m, \psi_1) = I(c_m, \psi_1, \psi_2) = \int_{-1}^{+1} \exp \left[ -\frac{(x_1 - x_2)^2}{c_m^2} + j\psi_1(x_1 - x_2) \right] dx_1 dx_2$ .

a is the correlation radius of the refractive index of the medium, f is the focal length, k is the wave number, h is the length of the square aperture of the focusing system, y', y", z', z" are the coordinates of the points of observation. Some special cases are treated in order to illustrate the character of the correlation function as depending on the amount of the fluctuations and on the ratio of the size of the system to the correlation radius. The results can be used to study the correlation function of the far field of an antenna. There are 3 figures.

SUBMITTED: June 2, 1961

Card 2/2

S/109/63/008/003/005/027 D413/D308

AUTHOR:

Shifrin, Ya. S.

TITLE:

Field statistics of a linear antenna

PERIODICAL:

Radiotekhnika i elektronika, V. 8, no. 3, 1963,

400-407

TEXT: In normally statistical estimation of the parameters of antenna systems, the errors in the phase-amplitude distribution of the sources are assumed to be small, and the correlation radius of the errors to be much smaller than the linear dimensions of the antenna. These assumptions may, however, be invalid for a number of cases, such as wind deformation or the effect of fluctuations in the incident wave. The author examines the statistics of the antenna field for any arbitrary errors and correlation radius, taking a linear cophased system of continuously distributed sources with random phase errors and assuming uniform distribution for the amplitude and dispersion of the

Card 1/2

Field statistics...

S/109/63/008/003/005/027 D413/D308

phase errors. A general expression for the radiation pattern of the antenna under these conditions is derived, and graphs of mean radiation patterns obtained for various combinations of dispersion and correlation radius are presented. These show that as the error dispersion increases, the pattern gradually changes to a monotone-decreasing form, with the power in the maximum decreasing; as the correlation radius increases, the pattern approaches its fluctuation-free form, with the power in the maximum increasing. The width of the main lobe of the mean radiation pattern is derived for the case of small phase errors, and the broadening of the beam is shown to be at maximum when the correlation radius is ~0.4 of the array length, Reference is also made to the corresponding results for errors that are not small. There are 8 figures.

SUBMITTED:

March 12, 1962

Card 2/2

# CIA-RDP86-00513R001549410014-2 'APPROVED FOR RELEASE: 08/25/2000

5/0106/64/000/009/0012/0017

ACCESSION NR: AP4045819

AUTHOR: Shifrin, Ya. S.; Tarasov, V. A.; Trashkov, P. S.

TITLE: Experimental investigation of some problems of long-distance tropospheric propagation of 10-cm-band radio waves. Part 2

SOURCE: Elektrosvyaz', no. 9, 1964, 12-17

TOPIC TAGS: radio communication, tropospheric propagation, radio wave, radio wave propagation, 10 cm wave propagation

ABSTRACT: Experiments which were conducted in the Autumn of 1961 and in the Summer of 1962 on 80, 205, and 255-km land routes are described. Both transmitting and receiving antennas had a 0.70-wide radiation pattern; the receiving antenna was rotated at 18° or 36° per sec. The angles of recording the radiation pattern were 1.8° or less and 3.6° or less for the speeds of antenna rotation of 18° and 36°, respectively; hence, the radiation patterns were regarded as

Card 1/2

L 17665-65 EEO-2/EWT(d)/FSF(h)/EWT(1)/EEC(k)-2/EEC-4/EEC(t)/EED-2 Pm-4/Pn-4/Pac-4/Pg-4/Pt-10/Pi-4/Pj-4/Pk-4/P1-4 AFWL/SSD/RAEM(a)/AFIC(b)/ESD(gs) RB/WS/WR
ACCESSION NR: AP4043713 S/0106/64/000/008/0001/0008

AUTHOR: Shifrin, Ya. S.; Tarasov, V. A.; Trashkov, P. S.

TITLE: Experimental investigation of some problems of long-distance tropospher radio-wave propagation in the 10-cm band

SOURCE: Elektrosvyaz', no. 8, 1964, 1-8

TOPIC TAGS: tropospheric radio wave propagation, autocorrelation function, signal fluctuation, signal fluctuation spectrum, radar of transmitter, angular diversity reception, space diversity reception, diversity reception

ABSTRACT: Two problems pertaining to long-distance tropospheric propagation of radio waves in the 10-cm band have been investigated. The first concerned the autocorrelation function and the fluctuation spectrum of signal levels. The investigations were carried out for distances of 120, 200, 250, and 350 km. A 200-kw pulse-radar transmitter was utilized. The radar antenna was a paraboloid of revolution of  $18\lambda$  in diameter (at half-power points, the width of the antenna pattern was 4.5°). An identical antenna was used by the receiver.

Card 1/3

#### CIA-RDP86-00513R001549410014-2 "APPROVED FOR RELEASE: 08/25/2000

0

L 17665-65 ACCESSION NR: AP4043713

Receiver sensitivity was of the order of  $10^{-13}$  w. From the output of receiver video-amplifier the signal was fed to a detector and then to a 1-f amplifier, and recorded on film or paper tape. The autocorrelation function  $R(\tau)$  was calculated by substituting an aggregate of discrete values for the continuous signal x(t). Quantization intervals At were 0.2 sec. The semianalytical method was used to calculate the fluctuation spectra on the basis of the experimental  $R(\tau)$  curves. The experimental data demonstrated that in long-distance tropospheric propagation, the signals are very non-stationary. The second problem studied was angular diversity reception. In order to find out the potentialites of such a method the decline in signal correlation during the separation of the primary exciters and the decrease of the mean signal level during withdrawal of the exciter from the focus were investigated experimentally in the summer of 1961 for distances of 60, 120, and 200 km by means of the same transmitting equipment as for the autocorrelation function. A 3 m paraboloid of revolution with a two-channel exciter served as the receiver. The exciter consisted of two grids formed by waveguides with a cross section  $72 \times 4$  mm. The design of the exciter made it possible to separate

Card 2/3

L 17665-65

ACCESSION NR: AP4043713

the channel electric centers in the range of 0--180 mm in the focal plane; at the same time the radiation pattern expanded between 0 and 7°. As a result of the investigation, it was concluded that as compared to the usual method of space diversity reception, angular reception is simpler and cheaper. On the other hand space diversity reception has the advantage of maintaining the mean signal level, while in an angular diversity reception the expansion of radiation patterns results in a decrease of the mean signal level. Orig. art. has: 8 figures and 4 formulas.

ASSOCIATION: none

SUBMITTED: 12Aug63


ENCL: 00

SUB CODE: EC

NO REF SOV: 006

OTHER: 002

Card 3/3



APPROVED FOR RELEASE: 08/25/2000 CIA-RDP86-00513R001549410014-2"

#### CIA-RDP86-00513R001549410014-2 "APPROVED FOR RELEASE: 08/25/2000

ACC NRI AM5027749

escriveral descriptions de la company de

Problems of investigating the troposphere by means of refractometers, the mean level of signals, meteorological conditions and topography, fluctuation of arrival angles and distortions of antennadirectivity patterns, losses in antenna gain, and quick and slow fadings of signal levels are discussed. The statistical characteristics of the signals at diversity reception in time, space, frequency and angle as well as the distortion of signals in the communication systems are also investigated. The long-distance propagation of signals in the communication systems are also investigated. The long-distance propagation-theory is analyzed, and the engineering method of calculating field intensity at long-distance tropospheric propagation is given. At present, there is no theory of Long-Distance Tropospheric Propagation which can be applied effectively enough in practice. Thus, in the investigation of that propagation, considerable attention has to be paid to experiments. The special characteristics of geographical conditions of the territory involved should be taken into consideration during the analysis of experimental data and in their practical application because the conditions of propagation in arctic and tropical climates differ from those existing over seas and continents. A considerable part of the monograph deals with the investigations of long-distance tropospheric propagation carried out over dry land routes, 800 km long, in the central part of the USSR under the general supervision of B. A. Vvedenskiy and A. G. Arenberg (up to 1957). V. I. Siforov investigated problems con-

Cord 2/10

```
nected with distortions and fluctuations of signals. References follow each chapter.

TABLE OF CONTENTS:

Foreword --

Ch. I. Radio Engineering Methods of Investigating the Troposphere Dielectric Constant -- 5

Bibliography -- 16

Ch. II. Results of Troposphere Dielectric Constant Measurements -- 17

1. Relationship between the mean value of the air refraction index and altitude. Standard radio-atmosphere -- 17

2. Fluctuations of the air refraction index -- 24

3. Some notions on the troposphere model -- 43

Bibliography -- 45

Ch. III. Average (mean) Signal Levels in Long Distance Tropospheric Propagation of Ultrashort Waves (LT. P U S W) -- 48
```

1. Equipment and measuring methods for the mean signal level 48 2. Signal attenuation function in LTP USW 54 3. Relationship between mean signal level and the distance 57 4. Relationship between mean signal level and the wavelength 63 5. Relationship of mean signal level and the shadow angles of both transmitting and receiving antennas 165 6. Diurnal and seasonal variations of mean signal level 72  Bibliography 75  Ch. IV. Effect of Air Refraction Index at the Earth Surface on the Mean Field Level in LTP USW 77 1. Correlation of the mean field level with the air refraction index at the Earth Surface 77 2. Possibility of predicting field intensity variations 81  Bibliography 86  Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities 88 1. Methods of measuring radiowave arrival angles and recording of instantaneous antenna directional patterns 89	3 6	AM5027749	anguming moth	ode for th	noon stenni	level l	.в		
4. Relationship between mean signal level and the wavelength 63 5. Relationship of mean signal level and the shadow angles of both transmitting and receiving antennas 165 6. Diurnal and seasonal variations of mean signal level 72  Bibliography 75  Ch. IV. Effect of Air Refraction Index at the Earth Surface on the Mean Field Level in ITP USW 77 1. Correlation of the mean field level with the air refraction index at the Earth Surface 77 2. Possibility of predicting field intensity variations 81  Bibliography 86  Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities 88 1. Methods of measuring radiowave arrival angles and recording of	2. S	Signal attenuat	ion function	in LTP US	<b>7</b> 54				
6. Diurnal and seasonal variations of mean signal level 72  Bibliography 75  Ch. IV. Effect of Air Refraction Index at the Earth Surface on the Mean Field Level in ITP USW 77  1. Correlation of the mean field level with the air refraction index at the Earth Surface 77  2. Possibility of predicting field intensity variations 81  Bibliography 86  Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities 88  1. Methods of measuring radiowave arrival angles and recording of	4. R	Relationship be	etween mean si	gnal level	. and the wave	length	63		
Ch. IV. Effect of Air Refraction Index at the Earth Surface on the Mean Field Level in ITP USW 77 1. Correlation of the mean field level with the air refraction index at the Earth Surface 77 2. Possibility of predicting field intensity variations 81 Bibliography 86 Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities 88 1. Methods of measuring radiowave arrival angles and recording of	6. D	transmitting an Diurnal and sea	d receiving a sonal variati	ntennas - .cns of mea	::65 un signal leve	1 72			
Mean Field Level in ICP USW 77  1. Correlation of the mean field level with the air refraction index at the Earth Surface 77  2. Possibility of predicting field intensity variations 81  Bibliography 86  Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities 88  1. Methods of measuring radiowave arrival angles and recording of	B1b11o	ography 75					.:		
Ch. V. Fluctuation of Radiowave Arrival Angles and Instantaneous Patterns of Antennas Directivities 88 1. Methods of measuring radiowave arrival angles and recording of	Mean 1. C	n Field Level i Correlation of index at the Ea	n ITP USW the mean fiel rth Surface.	77 d level wat 77	th the air re	fraction		•	
Patterns of Antennas Directivities 88  1. Methods of measuring radiowave arrival angles and recording of	Biblio	ography 86	`						
	Patt 1. M	terns of Antenn Methods of meas	as Directivit uring radiowa	ies 88 ve arrival	) . angles and r				
Card U/10	Card 1	<b>μ∕20</b>						٠	

ACC N2: AM5027749	
<ol> <li>Fluctuation of radiowave arrival angles in hor planes 92</li> <li>Instantaneous antenna directional patterns</li> </ol>	
Bibliography 102	
Ch. VI. Losses in Antenna Gain of IMP USW 103  1. Determination and methods of measuring losses 2. Experimental data on losses in antenna gain 3. Theoretical investigations on losses in antenna	- 108
Bibliography 120	
Ch. VII. Theories of Long Distance Tropospheric Propusal 122  1. Introductory remarks 122	pagation of
Bibliography 129	•
2. Theory of scattering radiowaves by tropospheric nonhomogeneities - 130	turbulent
Cord 5/10	

AM5027749

Bibliography -- 150

3. Reflection of radiowaves from dielectric nonhomogeneities of definite dimensions -- 151

Bibliography -- 171

4. Reflections of radiowaves from laminated tropospheric nonhomogeneities of random character -- 172

Bibliography -- 179

Ch. VIII. Engineering Method of Design-Calculation of Field Intensity Attenuation -- 180

1. Bacic rules of calculation method -- 181

2. Diffraction horizon (a distance, beginning of which, the value of the field intensity, calculated according to the diffraction formulas is smaller than the measured intensity) -- 182

3. Determination of field standard attenuation -- 182

4. Meteorological conditions correction -- 184

5. Local topography correction -- 185

6. Estimate of losses in antenna gain -- 185

7. Estimate of fadings -- 186

Bibliography -- 188

Ch. IX. Statistical Characteristics of the Envelope, Phase and Frequency of the Random Signal in LTP USW -- 189

1. Statistical characteristics of atmosphere dielectric constant signal components in LTP -- 189

2. Distribution laws for the envelopes and phase of various signal components -- 193

3. Distribution laws of sum-signal envelope -
4. Multi-dimensional distribution functions of instantaneous value of envelopes and phases of the spaced signals in minute intervals 207

5. Parameters of multi-dimensional amplitude and phase distribution functions of spaced signals -- 210

6. Statistical characteristics of instantaneous values of the envelopes of spaced signals in minute intervals -- 222

7. Statistical characteristics of instantaneous values of spaced signal phases in minute intervals -- 239

8. Statistical characteristics of instantaneous value of phase first derivatives of spaced signals in minute intervals -- 248

Card 7/10

ACC A	15.
	<sup>NR</sup> AM5027749
9.	Statistical characteristics of instantaneous values of the first derivative of phase in minute intervals 257
B1b1	1ography 260
σh	X. Experimental Investigations of Rapid and Slow Fadings in
-	P USW 262 Methods of measuring and processing experimental data 262 One-dimensional distribution functions of signal instantaneous
	values 264 One-dimensional distribution functions of signal averaged values-
	278 Period and frequency in rapid fluctuations of signal envelope-283
віы	liography 287
10	XI. Experimental Investigation of Signal Statistical Characterstics at Space, Frequency, Time and Angle Diversity Reception - 288  Space-diversity reception 288  Prequency-diversity reception 295
_	mi - 2 44 condition management on the 200
	Frequency-time diversity reception 305  Angle-diversity reception 307
	8/10

```
Bibliography -- 312

Ch. XII. Investigation of Amplitude-Frequency and Phase-Frequency Signal Characteristics at LTP -- 314

1. Measuring and processing methods of experimental data -- 314

2. Amplitude-frequency characteristics -- 321

3. Phase-frequency characteristics of LTP channel -- 325

4. Frequency characteristics of signal group time delay -- 334

Bibliography -- 350

Ch. XIII. Signal Distortion in LTP USW -- 351

1. Theoretical investigation of distortions appearing in multichannel FM LTP communication systems -- 352

2. Experimental investigation of distortion in LTP -- 384

3. Distortions appearing during TV transmission over tropospheric radio links -- 389

Bibliography -- 392

Appendix Automation of Signal Statistical Processing -- 394

1. Quantification of continuous signals and coding -- 395

2. Signal quantification instruments -- 397

Cord 9/10
```

SHIFRIN, Te.

Changes in U.S. agriculture since the Second World War. Vop.ekon. no.6:87-102 Je '56. (MERA 9:8)

### S/096/63/000/003/006/010 E194/E455

AUTHORS: Markin, V.F., Candidate of Technical Sciences,

Gutkin, I.A. Engheer, Kostyuk, A.G., Candidate of Technical

Sciences, Shifrin, Ye.L., Engineer

TITLE: The influence of transient heat-exchange on the

process of regulating gas-turbine sets

PERIODICAL: Teploenergetika, no.3, 1963, 38-42

TEXT: In governing a gas turbine it is not the amount of gas flow which is regulated (as is the case in a steam turbine) but the amount of heat applied to the flow. Under steady-state conditions a steady temperature distribution is achieved between the various parts of the gas duct and the gas flowing through it. However, under transient conditions, the gas duct may either give up heat to the gas or extract heat from it, thus temporarily modifying the influence of the regulator. This effect can be of considerable practical significance. The differential equation for a gas-turbine regenerator is derived in the form

$$\frac{d\theta}{dz} = \frac{\mu}{\tau_{\mu}} + \frac{\theta}{\tau_{\theta}} + \frac{\nu}{\tau_{\nu}} + \frac{\rho}{\tau_{\rho}} \qquad (8)$$

Card 1/2

The influence of transient ...

S/096/63/000/003/006/010 E194/E455

where  $\theta = \Delta T_e/T_{eo}$ ;  $\mu = \Delta B/B_o$ ;  $\nu = \Delta G/G_o$ ;  $\rho = \Delta \varepsilon/\varepsilon_o$ ; Te - air temperature beyond regenerator, 'K; B - rate of fuel consumption; G - rate of air consumption,  $\varepsilon$  - compression ratio. This equation was used to calculate the effect when a turbine picks up load and it is shown that because of transient cooling in the regenerator the temporary loss of output is greater than it otherwise would be. The problem cannot be overcome by increasing the regulator speed but a solution may be achieved by temporary over-regulation. The device used by the "Ekonomayzer" Works to achieve such temporary over-regulation of a gas turbine type  $\Gamma T Y - 6$  (GTU-6) is then described. In basic principle there is only one fuel-control valve, which over-travels in the first stage of the transient process and gradually returns to the correct setting. Two servo-motors are used in the regulator. Comparative test results on a gas turbine type GTU-6 with the normal regulator and with this special one are quoted for cases of picking up and throwing off 100% load. There is a substantial improvement in performance with the new regulator. The use of temporary over-regulation avoids the need to alter the Card 2/3.

5/096/63/000/003/006/010 E194/E455

The influence of transient ...

static characteristics of the regulation system; perfection has not yet been achieved but further improvement is possible. It should be noted that a regenerator does not always distort the should be noted that a regenerator does not always distort the transient process, but only in such cases when at different loads the temperature gradient between the regenerator wall and gas the temperature gradient between the regenerator wall and gas changes markedly. The greatest change occurs in gas turbines in which a compressor of flat characteristic runs at approximately constant speed. The main criterion in assessing the probable influence of the regenerator on the transient process is the gas temperature beyond the turbine. The more this changes on change of load the greater the influence of the regenerator on the transient process. There are 5 figures.

ASSOCIATION: Moskovskiy energeticheskiy institut - zavod
"Ekonomayzer" (Moscow Power Engineering Institute "Ekonomayzer" Works)

Card 3/3

GUTKIN, I.A., inzh.; SHIFRIN, Ye.L., inzh.; GOL'DZAND, L.D., inzh.; KIRAKOSYANTS, G.A., kand.tekhn.nauk.

Hydraulic system of control and protection of the OSPT-1150 turbine pump. Energomashinostroenie 9 no.9:11-14 S '63. (MIRA 16:10)

SHIFRIN, Ye.L., inzh.; GARKAVI, V.A., inzh.

Stability of the parallel operation of centrifugal pumps. Energomashinostroenie 10 no.7:8-11 J1 '64. (MIRA 17:9)

(MIRA 10:5)

Shill Alian, A.Ya.; Shifrina, A.G.

Sleep therapy in the compound treatment of chronic gunshot osteomyelitis. Trudy Inst. klin. i eksp. khir. i eksp. khir.

AN Kaz. SSR 1:114-120 '54

1. Iz kliniki obshchey khirurgii Kazakhskogo gosudarstvennogo meditsinskogo instituta im. V.M. Molotova.

(SLEEP--THERAPEUTIC USE) (OSTEOMYELITIS)

YUVACHEVA, N.Ya.; SHIFRINA, A.Sh., kand.tekhn. nauk, red.

[Mechanical working of titanium alloys; a bibliography] Mekhanicheskaia obrabotka titancvykh splavov; bibliograficheskii ukazatel'. Pod red. A.Sh.Shifrina. Leningrad, 1963. 16 p. (MIRA 16:9)

28(4), 15(8) AUTHORS:

Vasilevskaya, L. S., Shifrina, G. G.

SOV/32-25-6-49/53

TITLE:

Ftoroplast-4 as Platinum Substitute (Ftoroplast-4 kak

zamenitel' platiny)

PERIODICAL:

Zavodskaya Laboratoriya, 1959, Vol 25, Nr 6, pp 762-763 (USSR)

ABSTRACT:

Experiments were carried out in the course of which it was found that polytetrafluoroethylene ("Ftoroplast-4") (Ref 1) may be used, partly as a substitute of platinum, glass, and quartz for the production of laboratory devices. Cups of five different sizes were made of Ftoroplast foils (200 . 200 . 4 mm) and bars (60 mm long and 27 mm in diameter), produced in Russia. They were exposed to the effect of a mixture of hydrochloric- and nitrohydrochloric acid

at 100° (in the water bath) during 60 hours. Apart from this particularly pure reagents were evaporated in these plastic vessels and the residue investigated according to a spectral method of S. M. Solodovnik et al. Parallel experiments were made in platinum and quartz vessels. The results of analysis obtained (Table) show that the evaporation in Ftoroplast vessels at temperatures of up to

250-300 does not lead to a higher degree of impurities of the substance to be investigated and to a higher degree of dissolution

Card 1/2

Ftoroplast-4 as Platinum Substitute

SOV/32-25-6-49/53

of the plastic than it is the case with platinum. The Analiticheskaya komissiya pri GEOKhI AN SSSR (Analytical

Committee at the GEOKhi AS USSR) permitted the use of Ftoroplast

vessels. There are 1 table and 1 Soviet reference.

ASSOCIATION:

Gosudarstvennyy nauchno-issledovatel'skiy i proyektnyy institut redkometallurgicheskoy promyshlennosti (State Scientific Research-

and Planning Institute of the Industry of Rare Metals)

Card 2/2

CIA-RDP86-00513R001549410014-2" **APPROVED FOR RELEASE: 08/25/2000**